

## Nylon Cable Ties- Self-Lock Type

### ► Product Feature

- Versatile cable ties can be used in countless applications.
- One-piece construction for consistent performance and reliability.
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation.
- A variety of materials and colors is available for specific applications.
- For indoor or outdoor use



### ► Technical Information

- Material: Nylon 66
- Working Temp.: -40°C to 85°C
- Color: Nature or Black
- Flammability: UL94V-2
- Other properties: Halogen free

### ► Special Requirements Available

- Flame retardant(UL 94V-0).
- UV Resistant, ideal for outdoor use with lots of sunlight.
- Heat stabilized(up to +105°C). Ideal for environment with high temperature.
- Ideal for environment requires low flammability and low smoke, such as public transportation, tunnel, etc.

Item No.	Width		Length		Thickness		Max. Bundle Dia.		Min. Bundle Dia.		Min. Tensile Strength		Hand Tool
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs	
HT-2.5*60	2.5	0.098	60	2.36	1.00	0.039	11	0.43	2.0	0.079	80	18	LPA
HT-2.5*80			80	3.15	1.00	0.039	16	0.63	2.0	0.079			
HT-2.5*100			100	3.94	1.00	0.039	22	0.87	2.0	0.079			
HT-2.5*120			120	4.72	1.00	0.039	30	1.18	2.0	0.079			
HT-2.5*150			150	5.91	1.00	0.039	35	1.38	2.0	0.079			
HT-2.5*200			200	7.87	1.00	0.039	50	1.97	2.0	0.079			
HT-3.6*100	3.6	0.142	100	3.94	1.30	0.051	22	1.30	3.0	0.118	178	40	LPA
HT-3.6*140			140	5.51	1.30	0.051	33	1.38	3.0	0.118			
HT-3.6*150			150	5.91	1.30	0.051	35	1.65	3.0	0.118			
HT-3.6*180			180	7.09	1.30	0.051	42	1.97	3.0	0.118			
HT-3.6*200			200	7.87	1.30	0.051	50	2.56	3.0	0.118			
HT-3.6*250			250	9.84	1.30	0.051	65	2.76	3.0	0.118			
HT-3.6*280			280	11.02	1.30	0.051	70	3.15	3.0	0.118			
HT-3.6*300			300	11.81	1.30	0.051	80	3.94	3.0	0.118			
HT-3.6*350			350	13.78	1.30	0.051	100	3.94	3.0	0.118			
HT-3.6*370			370	14.57	1.30	0.051	105	4.13	3.0	0.118			
HT-3.9*395	3.9	0.154	395	15.55	1.30	0.051	110	4.33	3.0	0.118	180	42	LPA
HT-4.0*445	4.0	0.157	445	17.52	1.30	0.051	125	4.92	3.0	0.118	200	45	
HT-4.0*495			495	19.49	1.30	0.051	165	6.50	3.0	0.118			

Item No.	Width		Length		Thickness		Max. Bundle Dia.		Min. Bundle Dia.		Min. Tensile Strength		Hand Tool					
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs						
HT-4.8*120	4.8	0.189	120	4.72	1.50	0.059	30	1.18	3.5	0.138	222	50	LPA					
HT-4.8*150			150	5.91	1.50	0.059	40	1.57	3.5	0.138								
HT-4.8*180			180	7.09	1.50	0.059	42	1.65	3.5	0.138								
HT-4.8*200			200	7.87	1.50	0.059	50	1.97	3.5	0.138								
HT-4.8*280			280	11.02	1.50	0.059	70	2.76	3.5	0.138								
HT-4.8*300			300	11.81	1.50	0.059	80	3.15	3.5	0.138								
HT-4.8*350			350	13.78	1.50	0.059	90	3.54	3.5	0.138								
HT-4.8*370			370	14.57	1.50	0.059	98	3.86	3.5	0.138								
HT-4.8*380			380	14.96	1.50	0.059	102	4.02	3.5	0.138								
HT-4.8*400			400	15.75	1.50	0.059	105	4.13	3.5	0.138								
HT-4.8*430			430	16.93	1.50	0.059	120	4.72	3.5	0.138								
HT-4.8*450			450	17.72	1.50	0.059	130	5.12	3.5	0.138								
HT-4.8*500			500	19.69	1.50	0.059	150	5.91	3.5	0.138								
HT-7.2*150			7.2	0.283	150	5.91	1.60	0.063	35	1.38				6.0	0.236	534	120	LPA
HT-7.2*200					200	7.87	1.60	0.063	50	1.97				6.0	0.236			
HT-7.2*250	250	9.84			1.60	0.063	65	2.56	6.0	0.236								
HT-7.2*300	300	11.81			1.60	0.063	80	3.15	6.0	0.236								
HT-7.2*350	350	13.78			1.60	0.063	90	3.54	6.0	0.236								
HT-7.2*380	380	14.96			1.60	0.063	100	3.94	6.0	0.236								
HT-7.2*400	400	15.75			1.60	0.063	105	4.13	6.0	0.236								
HT-7.2*450	450	17.72			1.60	0.063	110	4.33	6.0	0.236								
HT-7.2*500	500	19.69			1.60	0.063	150	5.91	6.0	0.236								
HT-7.2*530	530	20.87			1.60	0.063	160	6.30	6.0	0.236								
HT-7.2*550	550	21.65			1.60	0.063	165	6.50	6.0	0.236								
HT-7.6*250	7.6	0.299			250	9.84	1.60	0.063	65	2.56	8.0	0.315	560	130	LPA			
HT-7.6*300					300	11.81	1.60	0.063	80	3.15	8.0	0.315						
HT-7.6*350					350	13.78	1.60	0.063	90	3.54	8.0	0.315						
HT-7.6*380					380	14.96	1.60	0.063	100	3.94	8.0	0.315						
HT-7.6*400			400	15.75	1.60	0.063	105	4.13	8.0	0.315								
HT-7.6*450			450	17.72	1.60	0.063	110	4.33	8.0	0.315								
HT-7.6*500			500	19.69	1.60	0.063	150	5.91	8.0	0.315								
HT-7.6*550			550	21.65	1.60	0.063	165	6.50	8.0	0.315								
HT-9*400			9.0	0.354	400	15.75	1.90	0.075	105	4.13	10.0	0.394				778	175	LPA
HT-9*450					450	17.72	1.90	0.075	118	4.65	10.0	0.394						
HT-9*500	500	19.69			1.90	0.075	150	5.91	10.0	0.394								
HT-9*550	550	21.65			1.90	0.075	160	6.30	10.0	0.394								
HT-9*600	600	23.62			1.90	0.075	170	6.69	10.0	0.394								
HT-9*650	650	25.59			1.90	0.075	185	7.28	10.0	0.394								
HT-9*700	700	27.56			1.90	0.075	190	7.48	10.0	0.394								
HT-9*750	750	29.53			1.90	0.075	200	7.87	10.0	0.394								
HT-9*760	760	29.92			1.90	0.075	205	8.07	10.0	0.394								
HT-9*800	800	31.50			1.90	0.075	230	9.06	10.0	0.394								
HT-9*850	850	33.46			1.90	0.075	240	9.45	10.0	0.394								
HT-9*900	900	35.43			1.90	0.075	265	10.43	10.0	0.394								
HT-9*1000	1000	39.37			1.90	0.075	300	11.81	10.0	0.394								
HT-9*1100	1100	43.31			1.90	0.075	335	13.19	10.0	0.394								
HT-9*1200	1200	47.24			1.90	0.075	370	14.57	10.0	0.394								
HT-12*650	12	0.472	650	25.59	2.20	0.087	185	7.28	16.0	0.630	1112	250	LPA					
HT-12*900			900	35.43	2.20	0.087	265	10.43	16.0	0.630								
HT-12*1000			1000	39.37	2.20	0.087	300	11.81	16.0	0.630								

- Please add "N" for Nature, or "B" for Black Color.
- special color and size available, please contact with STEMCO Customer Service.
- For information on installation tools, refer to Hand Tools pages.