

Stainless Steel Cable Ties- Ball-Lock Fully Coated

► Product Feature

- Fully coated vision will prevent static electricity.
- Polyester coated band provide additional edge protection, prevent the corrosion between dissimilar materials.

► Technical Information

- Material: Stainless Steel Grade 304 or 316
- Coating: Polyester; Nylon 11 & Pvc
- Working Temp.: -80°C to 150°C
- Description: Entirely Black
- Flammability: Fireproof
- Other Properties: UV-resistant, Halogen free, non toxic



Item No.	Width		Length		Thickness		Max. Bundle Dia.		Min. Bundle Dia.		Min. Tensile Strength		Recommended Installation Tool
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs	
Standard Cross Section													
SSC-4.6*100	4.6	0.18	100	3.9	0.35	0.014	25	1.00	12.7	0.50	710	160	LQD-S LQG LBG
SSC-4.6*150			150	5.9			37	1.46					
SSC-4.6*200			200	7.9			50	1.97					
SSC-4.6*250			250	9.8			63	2.48					
SSC-4.6*300			300	11.8			76	2.99					
SSC-4.6*350			350	13.8			89	3.50					
SSC-4.6*400			400	15.7			102	4.02					
SSC-4.6*450			450	17.7			115	4.53					
SSC-4.6*500			500	19.7			128	5.04					
SSC-4.6*550			550	21.7			141	5.55					
SSC-4.6*650			650	25.6			167	6.57					
SSC-4.6*800			800	31.5			193	7.60					
Light-Heavy Cross Section													
SSC-6.4*150	6.4	0.25	150	5.9	0.35	0.014	37	1.46	12.7	0.50	900	200	LQD-S LQG LBG
SSC-6.4*200			200	7.9			50	1.97					
SSC-6.4*250			250	9.8			63	2.50					
SSC-6.4*300			300	11.8			76	3.00					
SSC-6.4*350			350	13.8			89	3.51					
SSC-6.4*400			400	15.7			102	4.00					
SSC-6.4*450			450	17.7			115	4.50					
SSC-6.4*500			500	19.7			128	5.00					
SSC-6.4*550			550	21.7			141	5.56					
SSC-6.4*600			600	23.6			160	6.30					
SSC-6.4*800			800	31.5			193	7.60					

Item No.	Width		Length		Thickness		Max. Bundle Dia.		Min. Bundle Dia.		Min. Tensile Strength		Recommended Installation Tool
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs	
Heavy Cross Section													
SSC-7.9*150	7.9	0.31	150	5.9	0.35	0.014	37	1.46	12.7	0.50	1112	250	LQD-S LQG LBG
SSC-7.9*200			200	7.9			50	1.97					
SSC-7.9*250			250	9.8			63	2.50					
SSC-7.9*300			300	11.8			76	3.00					
SSC-7.9*350			350	13.8			89	3.50					
SSC-7.9*400			400	15.7			102	4.00					
SSC-7.9*450			450	17.7			115	4.50					
SSC-7.9*500			500	19.7			128	5.00					
SSC-7.9*550			550	21.7			141	5.56					
SSC-7.9*600			600	23.6			154	6.07					
SSC-7.9*650			650	25.6			167	6.58					
SSC-7.9*800			800	31.5			193	7.60					
SSC-7.9*1000			1000	39.4			206	8.12					
Extra-Heavy Cross Section													
SSC-12*350	12	0.47	350	13.8	0.45	0.018	78	3.07	25.4	1.00	2000	450	LQD-S
SSC-12*400			400	15.7			102	4.02					
SSC-12*500			500	19.7			128	5.04					
SSC-12*600			600	23.6			154	6.06					
SSC-12*750			750	29.5			188	7.40					
SSC-12*900			900	35.4			228	8.98					
SSC-12*1100			1100	43.3			278	10.94					
SSC-12.7*350	12.7	0.50	350	13.8	0.45	0.018	78	3.07	25.4	1.00	2000	450	LQD-S
SSC-12.7*400			400	15.7			102	4.02					
SSC-12.7*500			500	19.7			128	5.04					
SSC-12.7*600			600	23.6			154	6.06					
SSC-12.7*750			700	27.6			188	7.40					
SSC-12.7*900			900	35.4			228	8.98					
SSC-12.7*1100			1100	43.3			278	10.94					
Super-Heavy Cross Section													
SSC-15*350	15	0.59	350	13.8	0.45	0.018	78	3.07	25.4	1.00	3000	675	LQD-S
SSC-15*450			450	17.7			108	4.25					
SSC-15*600			600	23.6			148	5.83					
SSC-15*750			750	29.5			184	7.24					
SSC-15*900			900	35.4			220	8.66					
SSC-15*1100			1100	43.3			272	10.71					
SSC-15.9*350	15.9	0.63	350	13.8	0.45	0.018	78	3.07	25.4	1.00	3000	675	LQD-S
SSC-15.9*450			450	17.7			108	4.25					
SSC-15.9*600			600	23.7			148	5.83					
SSC-15.9*750			750	27.6			184	7.24					
SSC-15.9*900			900	31.5			220	8.66					
SSC-15.9*1100			1100	39.4			272	10.71					

- Other lengths available, contact STEMCO Customer Service.
- For information on installation tools, refer to Hand Tools pages.
- Please add the material grade by the end of the item number.